





**HT400 HydroSeeder®**



**HT330 HydroSeeder®**



**Power**

John Deere 4045HFC09 Tier 4 Final Diesel, 173 HP (129kW), industrial water cooled diesel engine. Vibration Isolated. Control panel with digital information display, throttle, pump on/off, horn, agitator speed and direction controls and E-Stop. Additional engine start/stop switch and E-Stop button is located on the bumper.

**Engine Safety System**

Engine ECU with self-diagnostics, including low oil pressure and high temperature shutoff

**Tank Size**

**HT330:** 3350 Gallon (12,681 Liter) Liquid Capacity  
**HT330:** 3000 Gallon (11,356 Liter) Working Capacity  
**HT400:** 3975 Gallon (15,047 Liter) Liquid Capacity  
**HT400:** 3600 Gallon (13,627 Liter) Working Capacity

**Fuel Tank Capacity**

50 Gallon ( 189.3 Liter)

**Pump**

**Centrifugal:** 6" x 3" (15.2 cm x 7.6 cm), 530 gpm @ 200 psi, 1.25" solid clearance  
**Vortex:** 6" x 3" (15.2 cm x 7.6 cm), 465 gpm @ 150 psi, 3" solid clearance

**Pump Drive**

Hydrostatically driven

**Agitation**

Twin mechanical agitators with helical paddle orientation and liquid recirculation

**Agitator Drive System**

Reversible, variable speed hydraulically driven  
 Lower Agitator: 0-150 RPM  
 Upper Agitator: 0-175 RPM

**Discharge Distance**

Greater than 300 ft. (91.4m) from discharge tower

**Material Capacity**

**HT330:** Granular Solids: 10,000 lbs. (4535.9 kg)  
**HT330:** Fiber Mulch: 1,500 lbs. (680.4 kg)  
**HT400:** Granular Solids: 12,400 lbs. (5624.5 kg)  
**HT400:** Fiber Mulch: 1,800 lbs. (816.5 kg)

**Material Carrying Capacity**

**HT330:** 50 lbs. / sq. ft. (4,800 lbs.)  
 244.1 kg / sq. m (2177.2 kg)  
**HT400:** 50 lbs. / sq. ft. (6,400 lbs.)  
 244.1 kg / sq. m (2903 kg)

**Nozzles**

(2) Narrow Fan, (2) Wide Fan, (2) Long Distance

**Empty Weight**

**HT330:** 14,000 lbs. (6350.3 kg)\*  
**HT400:** 15,000 lbs. (6803.9 kg)\*

**Working Weight**

**HT330:** 40,550 lbs. (18393.2 kg)\*\*  
**HT400:** 46,860 lbs. (21255.3 kg)\*\*

**Loading Hatch**

Raised, sealed hatch with 24-1/2" x 29-1/2" opening and integrated, pivoted stainless steel bag cutter with safety grate

**Bale Grinder**

Agitator with integrated mulch bale grinder for faster material loading

**Optional Equipment**

Stainless Steel Tank and Lids, Stainless Steel Agitator, Hose Reel Package w/ 1-1/4" Hose, Hose Reel Package w/ 1-1/2" Hose, Second Boom, Air Flush, Hardened Pump, Additional Fill Port, Rear Spray Bar, Front Flushers, Cab Controls

Note: Weight and specs subject to change after testing.

\* Empty weight includes 50 gal. of fuel and all engine and hydraulic fluids

\*\* Working weight includes one full load of fiber mulch and water with no stored materials on deck.

FINN Corporation has a policy of continuous product improvement, and reserves the right to change design and specifications without notice.

HydroSeeder® and the FINN Design® Logo are registered trademarks of FINN Corporation.

